

**TVT**

Secure The World With You

[www.tvt.net.cn](http://www.tvt.net.cn)



# TD-9441S2

4 MP Network IR Water-proof  
Bullet Camera

**TVT**

TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 5F, North Block, CE Lighting House, Hi-Tech Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China 518057


Tel: +86-755-3330 6001

Fax: +86-755-3330 6002

Web site: [www.tvt.net.cn](http://www.tvt.net.cn)

E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)


## 4 MP Network IR Water-proof Bullet Camera



### Features

- 4MP (2592 × 1520) H.265 coding
- Max. resolution: 2592 × 1520
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- 3D DNR, digital WDR
- Support smart alarm such as video exception, line crossing, intrusion, etc.
- ROI coding
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- Support P2P
- IP66 ingress protection
- Support three streams

### Dimensions



### Available Accessories



TD-YXH0201

### Specifications

Specifications	Model	TD-9441S2
<b>Camera</b>		
Image Sensor		1 / 3 "CMOS
Image Size		2592 × 1520
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Iris Type		Fixed Iris
Min. Illumination		0.05 lux @F1.2,AGC ON; 0 lux with IR
Lens		3.6 mm@F1.6, horizontal field of view: 85° (2.8 mm optional)
Lens Mount		M12
Day & Night		ICR
Wide Dynamic Range		120dB
Digital NR		2D / 3D DNR
Angle Adjustment		Any Angle
<b>Image</b>		
Video Compression		H.265 / H.264 / MJPEG
H.265 Compression Standard		Main Profile @Leve4.1 High Tier
Resolution		4MP (2592×1520), 2K (2560×1440), 3MP (2304×1296), 3MP (2048×1536), 1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
Main Stream		60Hz: 4MP(1~20fps) / 2K(1~20fps) / 3MP(1~30fps) / 1080P(1~30fps) / 720P(1~30fps) 50Hz: 4MP(1~20fps) / 2K(1~20fps) / 3MP(1~25fps) / 1080P(1~25fps) / 720P(1~25fps)
Bit Rate		128 Kbps ~ 8 Mbps
Bit Rate Type		VBR / CBR
Quality		Five levels under VBR; Freely adjustable under CBR
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, Antiflicker, etc. adjustable through client software or web browser
ROI		Each ROI to be configured separately
<b>Interfaces</b>		
Network		RJ45
<b>Functions</b>		
Remote Monitoring		IE browsing,CMS remote control
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol		TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol		ONVIF
Storage		Network remote storage
Smart Alarm		Motion alarm
Smart Analysis		Video exception, line crossing, intrusion, etc.
PoE		Yes
IR Distance		10 ~ 20 m
Ingress Protection		IP66
<b>Others</b>		
Power Supply		DC12V / PoE
Power Consumption		< 2.5W
IR Consumption ON		< 6.5W
Operating Environment		- 20 °C ~ 50 °C, 10 % ~ 90 % relative humidity
Dimensions ( mm )		Φ70 × 156
Weight ( net )		370g
Installation		Wall mounting, pendent mounting

### Available Model

Available Model	TD-9441S2 ( D / PE / IR1 )
-----------------	----------------------------