

**TVT**

**Secure The World With You**

[www.tvt.net.cn](http://www.tvt.net.cn)



# TD-9545E2

**4 MP Network IR Water-proof  
Dome Camera**

**TVT**

TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 5F, North Block, CE Lighting House, Hi-Tech Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China 518057


Tel: +86-755-3330 6001

Fax: +86-755-3330 6002

Web site: [www.tvt.net.cn](http://www.tvt.net.cn)

E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)


## 4 MP Network IR Water-proof Dome Camera



### Features

- 4MP (2592 × 1520) H.265 full real time coding
- Max. resolution: 2592 × 1520
- ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- Third generation of dot matrix LED IR lights, small size, efficient heat dissipation, long lifespan
- 3D DNR, physical WDR
- Support HLC, BLC and defogging
- Support electrical zoom
- ROI coding
- Support local CVBS video output and one-way audio
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- Support P2P
- IP66 ingress protection
- Support three streams

### Dimensions



### Available Accessories



TD-YXH0201

TD-YZJ0802

TD-YZJ0402

### Specifications

Specifications	Model	TD-9545E2
<b>Camera</b>		
Image Sensor		1 / 3 "CMOS
Image Size		2688 × 1520
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Auto Iris		Fixed Iris
Min. Illumination		0.05 lux @F1.2, AGC ON; 0 lux with IR
Lens		3.3 ~ 12 mm @F1.4, angle of view : 80°~38°
Lens Mount		Φ14
Day & Night		ICR
Wide Dynamic Range		120dB
BLC		Yes
HLC		Yes
Defogging		Yes
Digital NR		2D / 3D DNR
Angle Adjustment		Pan : 0°~360°, Tilt : 0°~90°, Rotation : 0°~360°
<b>Image</b>		
Video Compression		H.265 / H.264 / MJPEG
H.265 Compression Standard		Main Profile @Level4.1 High Tier
Resolution		4MP ( 2592×1520 ), 2K ( 2560×1440 ), 3MP ( 2304×1296 ), 1080P ( 1920×1080 ), 720P ( 1280×720 ), D1, CIF, 480×240
Main Stream		60Hz : 4MP ( 1 ~ 30fps ) / 2K ( 1 ~ 30fps ) / 3MP ( 1 ~ 30fps ) / 1080P ( 1 ~ 30fps ) / 720P ( 1 ~ 30fps ) 50Hz : 4MP ( 1 ~ 25fps ) / 2K ( 1 ~ 25fps ) / 3MP ( 1 ~ 25fps ) / 1080P ( 1 ~ 25fps ) / 720P ( 1 ~ 25fps )
Bit Rate		64 Kbps ~ 10 Mbps
Encode Mode		VBR / CBR
Quality		Five levels under VBR; Freely adjustable under CBR
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Audio Compression		G711A / U
ROI		Each ROI to be configured separately
<b>Interfaces</b>		
Network		RJ45
Audio		MIC IN × 1
Video Output		CVBS video output ( BNC × 1 )
<b>Functions</b>		
Remote Monitoring		IE browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol		TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol		ONVIF, GB-T/28181-2011
Storage		Network remote storage
Smart Alarm		Motion alarm
PoE		Yes
IR Distance		20 ~ 30 m
Water-proof		IP66
<b>Others</b>		
Power Supply		DC 12V / PoE
Power Consumption		< 2.5W
IR Consumption ON		< 5.5W
Operating Environment		- 20 °C ~ 50 °C, 10 % ~ 90 % humidity
Dimensions ( mm )		Φ109 × 130
Weight ( net )		689g
Installation		Pendent mounting ( Wall mounting available with the junction box and bracket )

### Available Model

Available Model	TD-9545E2 ( D / AZ / PE / AR2 )
-----------------	---------------------------------